

Xtona® 1512-z

Mid-Range Desktop Zero Client



Xtona® 1512-z

Fully featured

- Linux Gio2-z Operating System
- Citrix® HDX™ Ready
- Optional remote management software if required.
- VIA C7-M 1GHz Processor (North Bridge: VIA VX855)
- 1GB RAM
- Very small footprint - 19cm high x 14.2cm deep
- Highly reliable fanless design - very low power consumption
- 5 USB ports
- In-built 10/100/1000 Networking
- 32 Bit graphics

Green Credentials

With very low average power consumption of 7 watts, the Energy Star 5.0 rated Xtona®1512-z is far more efficient than a PC. It is also substantially lower than the majority of its competitors.

The VXL, Xtona 1512-z, desktop zero client built for the Citrix® environment.

The new Xtona 1512-z desktop provides Citrix® users with all the benefits of accessing XenDesktop® and XenApp™ and with the option to manage a desktop through VXL's world renowned management software, 'XLmanage'.

Additional benefits include faster processing speeds whenever server side rendering is required and a very low energy consumption, 7 watts, which translates into a massive saving when compared to a standard PC (up to \$70 per year per unit).

As you'd expect the Xtona 1512-z is compatible with most industry protocols especially HDX™ and comes complete with a fast 1GHz processor, 1GB RAM, five USB's and DVI-I interface. Backed by VXL's comprehensive worldwide support network and an impressive three year warranty, the new Xtona 1512-z represents an unbeatable combination of affordability, performance, quality and service.



About VXL

VXL is one of the world's largest suppliers of thin clients. Established in 1976, VXL has grown steadily and now has over three hundred people worldwide – with offices in Germany, France, India, the United States and the United Kingdom. The company's headquarters are in Bangalore, India.



CITRIX® partner

Solution Partner

Xtona[®] 1512-z

Part No

Xtona 1512-z - FOR5 0 MB Flash / 1 GB RAM

Model

Xtona 1512-z Linux Gio2-z
Operating System

Standard Client Software

Citrix[®] HDX[™] with
repurposing options

Processor

- VIA C7-M Processor (North Bridge: VIA VX855)

System Memory

- RAM: 1 GB

Display Support

- Display Data Control (DDC) for automatic setting of resolution and refresh rate
- Video RAM: 32/64/128 MB. Selectable from BIOS (default 32MB). Display res. 4:3 up to 1920x1440 32bit colour. Widescreen up to 2048 x 1152 32bit colour.

Interfaces

- 5 x USB 2.0
- 1 x DVI-I port
- Built-in Kensington Security Slot

Networking

- Autosensing, 10/100/1000 Ethernet, RJ-45
- Wake On Lan
- PXE boot

Audio

- Line Out
- Mic

Environmental

- Temperature Range :
Powered on: 5 to 35 °C
- Powered off: -20 to 60 °C
- Convectional cooling, fanless design
- Humidity : 20% to 80% maximum, non-condensing

Physical Characteristics

- External power adapter with full range autosensing AC adapter (100/240 V) for worldwide usage
- Height: 190 mm
- Depth: 142 mm
- Width: 36.5 mm
- Weight: Approx 0.7Kg

Software

- Citrix[®] HDX[™]
- PPTP VPN
- VNC Client
- VNC Shadowing
- CUPS Support
- Touch Screen Support
- Rexec command, RSH, SSH, LaunchPA , telnet, CMD standard

User Interface:

- User Interface Language: US English, French, German
- Keyboard language support: U.S. English Standard, French, German, Italian,U.K

English, 30 others included.

Management:

- Remote Shadowing

Regulatory Compliance

- Ergonomics: German EKI-ITB 2000
- Safety: cULus, TUV-GS,
- RF Interference: FCC B, CE, RoHS, WEEE, Energy Star 5.0

Warranty

- Three years limited warranty

Citrix[®], HDX[™], XenApp[™] & XenDesktop[®] are trademarks of Citrix Systems, Inc. and / or one or more of its subsidiaries, and may be registered in the United States Patent and Trademark office and in other countries.



Solution Partner



Head Office: 'House of Excellence', No 17 Electronics City, Hosur Road, Bangalore 560 100, India

Tel: +91 80 30222525 (5 lines) **Fax:** +91 80 28520095 **E-mail:** sales@vxl.net **Web:** www.vxl.net

European Headquarters: Carrington Business Park, Carrington, Manchester, UK M31 4DD

Tel: +44 (0) 16 17 75 47 55 **Fax:** +44 (0) 16 17 75 48 66 **E-mail:** sales@vxl.net

Regional Offices

France

Tel: +33 (0) 1 42 17 00 03
E-mail: sales@vxl.net

Germany

Tel: +49 (0) 8761 1093
E-mail: sales@vxl.net

United States

Tel: +1 281 305 1800
E-mail: sales@vxl.net